# Rec'd PGT/PTO 15 JUN 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



## 

(43) International Publication Date 8 July 2004 (08.07.2004)

(10) International Publication Number WO 2004/057867 A1

(51) International Patent Classification7: 5/00. 5/765

H04N 5/775,

(21) International Application Number:

PCT/IB2003/005463

(22) International Filing Date:

21 November 2003 (21.11.2003)

(25) Filing Language:

English

(26) Publication Language:

English


(30) Priority Data: 02080375.5

19 December 2002 (19.12.2002)

- (71) Applicant (for all designated States except US): KONIN-KLLIKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): KANG, I-Chih [NL/NL]; c/o Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL). SNLIDER, Freddy [NL/NL]; c/o Prof. Holstlaan 6,

- Agent: GROENENDAAL, Antonius, W., M.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Declaration under Rule 4.17:



time-shift mode in which the input task (20) is coupled to the recording task (24) and a replay task (26) is coupled to the decoding task (22). In different modes, different subsets of the tasks (20, 22, 24, 26) or all of the tasks (20, 22, 24, 26) are active. FIFO communication buffers (16a-d) are used to communicate between the tasks (20, 22, 24, 26). Switching between the video modes is realized by reassigning connections of tasks (20, 22, 24, 26) to respective ones of the communication buffers (16a-d), keeping is realized by reassigning connections of tasks (20, 22, 24, 26) to respective ones of the communication buffers (16a-d), keeping previous data in the reassigned FIFO communication buffers (16a-d). Tasks (20, 22, 24, 26) that are needed before and after a switch are kept continuously active, so that they continue to read from or write to the FIFO communication huffers (16a-d) to which they are connected. Reassignment of connections to communication buffers (16a-d) is preferably limited to points of time at transitions between transfer of closed Groups Of Pictures in the video streams.



#### 

CN. CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, IP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT. RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK,

EE, ES, FI, FR, GB, GR, HU, IE, II, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

### Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.